




RESEARCH&DEVELOPMENT OF AMERICA, INC.  
5420 DANIELS STREET STE.A, CHINO CALIF. 91710 (909) 634-9166 (909) 629-4722 FAX (909) 591-2198

[www.yoshimura-rd.com](http://www.yoshimura-rd.com)

1. Remove the stock turn signals.
2. Cut the stock turn signal wires on the harness side 2" behind the stock connector.
3. Strip wire ends 1/4" – 1/2" and determine positive (+) and negative (-) wires by temporarily connecting to Yoshimura turn signal.
4. Crimp the loose bullet connectors to harness wires accordingly.
5. Re-install and re-connect turn signal and check for proper function.

LED Turn Signal




RESEARCH&DEVELOPMENT OF AMERICA, INC.  
5420 DANIELS STREET STE.A, CHINO CALIF. 91710 (909) 634-9166 (909) 629-4722 FAX (909) 591-2198

[www.yoshimura-rd.com](http://www.yoshimura-rd.com)

1. Remove the stock turn signals.
2. Cut the stock turn signal wires on the harness side 2" behind the stock connector.
3. Strip wire ends 1/4" – 1/2" and determine positive (+) and negative (-) wires by temporarily connecting to Yoshimura turn signal.
4. Crimp the loose bullet connectors to harness wires accordingly.
5. Re-install and re-connect turn signal and check for proper function.

LED Turn Signal




RESEARCH&DEVELOPMENT OF AMERICA, INC.  
5420 DANIELS STREET STE.A, CHINO CALIF. 91710 (909) 634-9166 (909) 629-4722 FAX (909) 591-2198

[www.yoshimura-rd.com](http://www.yoshimura-rd.com)

1. Remove the stock turn signals.
2. Cut the stock turn signal wires on the harness side 2" behind the stock connector.
3. Strip wire ends 1/4" – 1/2" and determine positive (+) and negative (-) wires by temporarily connecting to Yoshimura turn signal.
4. Crimp the loose bullet connectors to harness wires accordingly.
5. Re-install and re-connect turn signal and check for proper function.

LED Turn Signal



RESEARCH&DEVELOPMENT OF AMERICA, INC.  
5420 DANIELS STREET STE.A, CHINO CALIF. 91710 (909) 634-9166 (909) 629-4722 FAX (909) 591-2198

[www.yoshimura-rd.com](http://www.yoshimura-rd.com)

1. Remove the stock turn signals.
2. Cut the stock turn signal wires on the harness side 2" behind the stock connector.
3. Strip wire ends 1/4" – 1/2" and determine positive (+) and negative (-) wires by temporarily connecting to Yoshimura turn signal.
4. Crimp the loose bullet connectors to harness wires accordingly.
5. Re-install and re-connect turn signal and check for proper function.

LED Turn Signal

